

NM12-250L

12V 250Ah / 10hr rate**BATTERY**
Genergy

Introduction

Genergy NML (Long life) Series is designed for solar and renewable energy system. The series is featured of its long service life. It is widely used in solar and wind power system, UPS and power utility.


Battery Features

- Increase durability and deep cycle ability for heavy demand applications
- Low self-discharge
- Fully tank formed plates
- Low impurity electrolyte
- Spill proof / leak proof
- Multi-position usage
- ABS case and cover VO upon request
- Very high purity lead

Electrical Specification

Design floating Life @ 25°C (77°F)	10 years
Nominal Capacity @ 25°C /77°F	
20 hour rate 13.1A to 1.75Vpc	262 Ah
10 hour rate 25.55A to 1.75Vpc	255.5 Ah
Internal Resistance	
(Fully charged battery @ 25°C /77°F)	3.5mΩ
Max. Discharge Current @ 25°C /77°F	2500 A (5S)
Charge Methods: Constant voltage charge @ 25°C /77°F	
Cycle Use	14.7 ~ 14.9V
Max. Current	62 A
Standby Use	13.6 - 13.8V
Operating Temperature Range	-30 ~ 50°C
<i>Notes: battery voltage must be adjusted according to temperature.</i>	
<i>Please refer to our recommendation.</i>	
Self-Discharge	
<3% of capacity declined per month @ 25°C (77°F).	

Battery Picture & Terminal Layout



Dimension & Weight

Length	Dimension (± 2mm)			Total Height	Weight (± 2%)
	Width	Height			
522 mm	269 mm	220 mm		225 mm	75 kg
20.6 inch	10.6 inch	8.7 inch		8.9 inch	165.3 lbs

Typical Applications

- Solar/Wind Energy System
- Power Utility
- UPS/EPS

Certificates



Constant Current Discharge (Amperes @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	611.8	467.0	405.3	343.5	295.7	263.9	246.1	228.3	210.7	195.9	184.9	101.01	74.26	61.11	49.97	26.70	13.48
1.65	581.0	443.5	385.2	326.9	282.6	252.0	235.4	218.8	202.4	188.8	178.9	96.68	71.49	58.68	47.87	26.06	13.22
1.70	557.0	425.2	370.0	314.8	273.6	243.7	227.7	211.7	196.0	183.0	173.9	93.32	69.85	57.30	46.74	25.81	13.22
1.75	531.3	405.5	353.5	301.4	263.3	234.4	219.6	204.7	190.1	178.1	170.1	90.66	68.35	56.04	45.74	25.55	13.10
1.80	503.8	384.6	336.1	287.6	253.0	225.0	211.0	197.0	183.2	172.2	165.0	87.30	66.71	54.66	44.61	25.13	12.98

Constant Power Discharge (Watts/cell @ 25°C /77°F)

V/cell	10min	15min	20min	25min	30min	35min	40min	45min	50min	55min	1hr	2hr	3hr	4hr	5hr	10hr	20hr
1.60	1062.5	811.1	713.8	616.5	534.2	484.8	450.3	415.9	383.0	356.9	334.5	187.30	136.19	113.21	93.24	52.24	27.56
1.65	1024.8	782.3	689.9	597.5	520.1	471.9	438.8	405.6	374.1	349.3	328.1	183.50	134.94	111.96	91.98	51.74	27.56
1.70	985.4	752.2	664.3	576.3	503.4	456.9	425.5	394.1	364.2	341.2	321.8	179.06	132.42	110.01	90.60	50.73	27.19
1.75	942.6	719.5	636.5	553.4	485.4	440.7	411.0	381.3	353.2	331.9	314.2	173.37	128.65	107.31	88.96	50.35	26.70
1.80	896.3	684.2	606.5	528.8	466.1	423.1	395.2	367.2	340.8	321.2	305.3	167.23	125.26	104.61	86.95	49.85	26.45

Subject to revision without notice. Please contact our sales representatives for latest version.

Web: www.genergybattery.com | Email: sales@genergybattery.com

NM12-250L

12V 250Ah / 10hr rate**BATTERY**
Genergy

Graphs

